



The functional color company®

ARASOL-10 in short:

- * Excellent balance between color strength and brightness / fluorescence
- * Improved light stability
- * NON-Melting / Thermoset
- * Decomposition T > 300 °C.
- * Heat stability: 90 °C / 2 minutes
- * Average particle size: 5 µm.
- * Hegman Grind: > 4,5

Regulatory & Ecotox

- All non-polymeric components are registered in EINECS and TSCA (including polymers in TSCA).
- All non-polymeric components are registered respectively preregistered in REACH
- EN71 part 3 conformity (purity requirement). Still tests have to be carried out on the final application.
- Heavy metals free (with exception of the natural values in the ppm range).

ARASOL-10 SERIES

PAINTS & SPRAY CANS

PAPER COATING

TARGET COATING

MARKING, NDT

CONTRAST FLUORESCENT POWDER

Technology & Applications

ARALON® ARASOL-10 is developed as an optimal choice for spray cans, paper coating and target coating applications. Fluorescent dyes are dissolved & bonded, encapsulated respectively embedded in a carrier. The solid solution is milled to optimal particle size. This technology results in ARALON® ARASOL-10 as excellent **STIR-IN** pigments.

While the technology of preparing fluorescent pigments allows individually higher values in the one or other pigment property, improvements on the one property side are often diminishing other pigment properties. The chemical nature of the ARALON® ARASOL-10 carrier as modified melamine formaldehyde resin and its pigment engineering deliver an optimum **balance between color strength, light fastness and fluorescence / brightness for targeted applications**. The resin ensures best STIR-IN quality, just mixing and homogenizing are sufficient to obtain final application products, no grinding is required, although this does not harm the pigment particles. Further advantages of the chosen pigment engineering are very **good staining performance**, while binder free formulations of ARASOL-10 series are easily washed out, conventional pigments and dyes leave their undesired high staining on the surfaces or fibers after washing. Best Hegman grind cut OFF ensures best performance in spray cans. ARASOL-10 is also optimally applied in textile, paper coating and target coating.

Light Fastness & Heat Stability

Light Fastness

ARASOL-10 series can partially resist the multiple factors, generally known to influence light fastness and, depending on the shade, values up to 5 on the BWS can be achieved.

Heat Stability

ARASOL-10 series can withstand temperatures of above 90 °C for up to 2 minutes without affecting the perceived shades. Resistance to even higher temperatures is possible but for shorter exposure time.

Storage & Shelf life

ARASOL-10 series products are stable. Provided they are stored in dry places at ambient temperatures (below 40 °C) the predicted shelf life is 60 months. However depending on the quality of storage conditions, products might be used beyond this shelf life period.

Available colors

ARASOL-109 UV	BLUE	
ARASOL-100	LEMON	
ARASOL-111	GREEN	
ARASOL-102	ORANGE-YELLOW	
ARASOL-103	ORANGE	
ARASOL-104	ORANGE-RED	
ARASOL-105	RED	
ARASOL-106	PINK	
ARASOL-107	MAGENTA	
ARASOL-119	BLUE	

The above shades are only indicative; computer screens and conventional printers cannot reproduce true fluorescent shades.

solvent resistance

The results of the following method are given on the next page: Mix 1 g pigment thoroughly for 10 seconds in 10 ml of Xylene : methyl-ethylketone (50:50) to get the complete pigment wetted. Store the mixture for 37 minutes into a water bath at 37°C . The solvent resistance of the pigment is determined by inverting and shaking the glass tube and observing how quick the pigment particles move or not. Bleeding is determined by diluting the filtrate 50 times and measuring the absorption. Worst bleeding is 1. Minor to non-Bleeding is 5.

Physical & Chemical properties

- Resin / Carrier: Modified melamine resin
- Volatile organic compounds: 0%
- Mineral oils: 0%
- Oil absorption: 52
- Particle size: 5 µm
- Grind: > 4,5 Hegman gauge
- Spec. Gravity: 1.4
- Bulking value: 0.4 g/ml

Packaging

Package = Minimal order

1 Carton BOX= 20 kg

Any given technical information is given on a purely informative basis.

ARALON cannot give any warranty for a particular use.

Action and observation	S: Solvent resistance scale	B: Bleeding Scale
Pigment moves after 1 to 15 shakes. All pigment parts are not attacked	5: Very good	5: Minor to NON-Bleeding
The first action above is not sufficient, 1 to 10 extra hard shakes are needed to let all pigment particles move	4: Good	4: Slight bleeding
After the 1 to 10 hard shakes, only a portion of the pigment moves, more than 10%	3: Moderate	3: Moderate bleeding
After the 1 to 10 hard shakes, only a portion of the pigment moves, more than 10% leaving a cone of attacked part	2: Poor	2: High bleeding
After the 1 to 10 hard shakes, the attacked part of the pigment is forming a gummy or sticky mass or the complete pigment is dissolved	1: Very poor	1: Heavy bleeding

		ARASOL-10	
		S	B
ALIPHATIC HYDRO CARBONS	Mixed hexanes	5	5
	Destillates 35-260°C	5	5
HYDRO CARBONS	Toluene	4	4
	Xylene	5	4
	Destillates 150-250°C	5	4-5
	Epoxidezed soya oil	5	5
	Acryl paints, moderate solvent	5	4-5
	Alkyd paints, moderate solvent	5	4-5

Mixing recommendations

AARASOL-119 BLUE or RASOL-109 UV BLUE 20 % Pigment Blue 15 dispersion	15 parts 1-3 parts	Fluorescent BLUE	PANTONE 801
ARASOL-111 or ARASOL-100 LEMON 20 % PIGMENT GREEN 7 dispersion	15 parts 1-3 parts	Fluorescent GREEN	PANTONE 802 / RAL6038
95-98% ARASOL-100 + 5-2% ARASOL-102		Fluorescent YELLOW	PANTONE 803 / RAL1026
ARASOL-102 (depending on the application 0 to 10 % ARASOL-100)		Fluorescent ORANGE-YELLOW	RAL 2007
ARASOL-103 / ARASOL-104, ratio depends on the application		Fluorescent ORANGE	RAL 2005
ARASOL-104 / ARASOL-105, ratio depends on the application		Fluorescent ORANGE-RED	RAL 3026
ARASOL-104 / ARASOL-105, ratio depends on the application		Fluorescent RED	RAL 3024
ARASOL-106 / ARASOL-107, ratio depends on the application		Fluorescent PINK	PANTONE 806
ARASOL-106 / ARASOL-107, ratio depends on the application		Fluorescent MAGENTA	PANTONE 807
ARASOL-109 UV BLUE with all other ARASOL- 10 shades		Less color strength without brightness loss	Conserved brightness
Neighboring ARASOL-10 shades		Optimal fluorescent intermediate colors	Inter-mediate shades
For more hiding power use ZnS pigment dispersions instead of TiO ₂ pigment dispersions to pre- serve optimal brightness, especially under UV light.			
ARASOL-10 at 10-30% in conventional inks of similar shade		Increase freshness of conven- tional colors	Fresh shades
2 - 5 % of conventional inks of similar shades to ARASOL-10 colors		Higher color strength without no- ticeable loss of brightness	Stronger shades



The functional color company®

About ARALON:

Today, ARALON – The NEW supplier of daylight fluorescent and functional pigments. Development, manufacturing and marketing of pigments for the paints & coatings (ARACO products), plastics (ARAPLAST), aerosols (ARASOL), and printing inks (ARAPRINT) industries only commenced in 2013 at its greenfield construction in 56412 Heiligenroth, Germany, half-way between Cologne and Frankfurt. ARALON's strengths are apparent in three key areas:

- State-of-the-art encapsulation technology coupled with modern and efficient manufacturing assets and lean operations capable of delivering best-in-class fluorescent pigments at competitive cost.
- Unique fluorescent ARAPLAST-melting pigments permitting coloration of thin olefin based films in single and multilayer packaging.
- Next generation ARAGEN-chemistry enabling unprecedented light stability of formaldehyde-free fluorescent pigments without compromising other performance attributes.

ARALON wants to surprise with best-in-class products, innovations that matter and prices hard to ignore – TRY US!

ARALON, What is behind the name and the logo?

ARALON was created as a name for our company based on the ARA, which is kind of colorful parrot. The wonderful and bright colors of the parrot's feathers are the result of light refraction through nano-sized holes in the natural polymer structure of the parrot feathers. Depending on the hole size and the number of feather layers results in an unlimited number of bright and colorful shades of light, seen by our eyes as being the color of the feathers themselves.

This has, for our company, a relevance of many kinds. Initially the brightness and purity of the parrot's colors is similar, but often less when compared to the brightness and purity of our fluorescent colors. Further, the colors of the feathers were created in completely natural way, which is for our R&D development, an orientation for the future horizons of the company.

ARALON GmbH
Auf der Birke 9
56412 Heiligenroth,
Germany

Telephone:

+ 49 2602 99 770-0

Fax:

+ 49 2602 99 77069

E-mail:

info@araloncolor.com

Website:

www.araloncolor.com

